



ALL DIMENSIONS IN MM (EXCEPT HTA AND STA IN °)

ALLE MASSE IN MM (AUSNAHME HTA UND STA IN °)

- STL** SEAT TUBE LENGTH
SITZROHRLÄNGE
- CSL** CHAINSTAY LENGTH
KETTENSTREBENLÄNGE
- TTL** TOP TUBE LENGTH
OBERROHRLÄNGE
- HTL** HEADTUBE LENGTH
STEUERROHRLÄNGE
- HTA** HEADTUBE ANGLE
STEUERROHRWINKEL
- RE** REACH
REACH
- SOH** STANDOVER HEIGHT
UBERSTANDSHÖHE
- [Icon]** HEAD SET DIAMETER (UPPER / LOWER)
STEUERSATZDURCHMESSER (OBEN / UNTEN)
- [Icon]** AXLE STANDARD (REAR / FRONT)
ACHSENSTANDARD (HINTEN / VORNE)
- [Icon]** BOTTOM BRACKET STANDARD
TRETLAGERSTANDARD
- [Icon]** SEAT POST DIAMETER
SITZSTÜTZENDURCHMESSER
- [Icon]** SHOCK HARDWARE (Ø 8 MM)
DÄMPFERBUCHSENMASSE (Ø 8 MM)
- [Icon]** SHOCK LENGTH
DÄMPFEREINBAULÄNGE
- [Icon]** SHOCK TRAVEL
DÄMPFERHUB
- [Icon]** FRONT FORK TRAVEL
FEDERWEG VORNE
- [Icon]** REAR WHEEL TRAVEL
FEDERWEG HINTEN
- [Icon]** STEM LENGTH
VORBAULÄNGE
- [Icon]** HANDLEBAR WIDTH
LENKERBREITE
- [Icon]** CRANK LENGTH
KURBELLENGE
- [Icon]** SEATTUBE BOTTLE MOUNT
FLASCHE SATTELROHR
- [Icon]** DOWNTUBE BOTTLE MOUNT
FLASCHE UNTERROHR

| | STL | CSL | TTL | HTL | HTA | STA | BB | WB | ST | RE | SOH | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] | [Icon] |
|------------------------------------|-----|-----|-----|-----|-----|-----|----|------|-----|-----|-----|---------|---------|--------|--------|-----------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| KATO FS 5.7 / 3.7 / 2.7 ALU | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | 420 | 430 | 575 | 110 | 69 | 75 | 15 | 1114 | 587 | 418 | 700 | 44 / 56 | 135/100 | BSA 68 | 31.6 | 30 / 22.2 | 200 | 51 | 130 | 130 | 60 | 760 | 175 | - | 0.5 | | |
| M | 460 | 430 | 600 | 120 | 69 | 75 | 15 | 1141 | 597 | 440 | 745 | 44 / 56 | 135/100 | BSA 68 | 31.6 | 30 / 22.2 | 200 | 51 | 130 | 130 | 60 | 760 | 175 | - | 0.75 | | |
| L | 500 | 430 | 625 | 130 | 69 | 75 | 15 | 1166 | 606 | 462 | 755 | 44 / 56 | 135/100 | BSA 68 | 31.6 | 30 / 22.2 | 200 | 51 | 130 | 130 | 75 | 760 | 175 | - | 0.75 | | |
| XL | 540 | 430 | 645 | 140 | 69 | 75 | 15 | 1182 | 615 | 475 | 785 | 44 / 56 | 135/100 | BSA 68 | 31.6 | 30 / 22.2 | 200 | 51 | 130 | 130 | 75 | 760 | 175 | - | 0.75 | | |